Standard Hook

Capacities up to 300 kg

A gripper that, when integrated in Quick-Lift SystemTM, meets the highest standards of ergonomics, working environment, safety and efficiency.

Easy to use, thanks to the outstanding responsiveness, regardless of load weight.

Exceptional safety is achieved using our intelligent control systems.

High cost efficiency through high reliability and long durability.

A Strong solution for quick and easy handling.

Article No: 012847 & 021061





Standard Handel with Disconnect Hook

Capacities up to 300 kg

The figures are to be seen as indications and will vary depending on lifting objects.











Article	No:	021061	

	TECHNICAL DATA		
	Article no:	012847 & 021061	
	Lifting Capacity:	Maximum lifting capacity for different objects when gripping center of gravity:	
3	Steel plate:	The standard hook is an option that is typically used when applications only requires "below the hook" devices like lifting slings, lifting chains, spreader bars and more. The standard hook comes complete with a built-in safety latch.	
	Operation:	Float mode or handle operation	
	Material	High strength steel	
	Surface Finish	Yellow paint	

Kundel Industries 1510 Ridge Road • Vienna Center • OH 44473 PH 330-259 9009 • FAX 330-259 9001 e-mail sales@binarusa.com • www.binarusa.com 2015-07-30 eng 1.01-US • www.binar.se

